

Convenient and easy to use installation projector with advanced technology and 5,000 ANSI lumens brightness in a low profile design.



Key Features

- XGA 1024 x 768 resolution
- 5,000 ANSI lumens white/color output
- 16 watt audio output
- 3000:1 contrast ratio
- HDMI 2 inputs
- 15,000 hours hybrid filter*
- 4,000 hours lamp life (Eco mode)**
- Quick Connection iPad App




Hitachi's installation-friendly CP-X8150 LCD projector is designed to provide maximum presentation impact in mid to large venue applications. It offers a versatile array of innovative, performance-enhancing features along with advanced video display technology providing bold, brilliant colors with incredible image clarity and uniformity. Plus, with motorized zoom, focus and superior lens shift, and a variety of lens options, the CP-X8150 is at the top of its class when it comes to installation flexibility. All this, and with a lower cost of ownership. For added peace of mind, Hitachi's CP-X8150 is also backed by a generous warranty and our world-class service and support programs.

CP-X8150

UNIQUE FEATURES

Center Lens Design



This feature makes it easy to align the projector with the center of the screen for faster and trouble-free setup.

DICOM® Simulation Mode



Images in DICOM (Digital Imaging and Communications in Medicine) Mode are reproduced with an advanced grayscale level. This mode is ideal for viewing grayscale medical images such as X-rays, and for training and educational purposes.

These projectors are not approved medical devices. They should not be used for actual medical diagnosis.

Motorized Zoom, Focus and Lens Shift Control



Allows for greater range of installation possibilities. With the motorized function you can make fine adjustments through the remote control or RS232/IP device.

Multiple Lens Options



In addition to the one SL702 short throw standard lens, four optional lenses are available: FL701 fixed; ML703 middle throw; LL704 long throw; and UL705 ultra-long throw.

Perfect Fit 2



Enables the user to adjust individual corners and sides independent of one another. Perfect Fit 2 provides vertical and horizontal digital correction of either barrel or pin cushion distortions. This feature helps correct geometric and complicated distortions. Perfect Fit 2 allows the projected image to fit correctly to the screen quickly and easily.

Projector Quick Connection iPad® App



Our iOS application offers full projector control and also provides the capability to display photos, document files and web site contents. Available for iPad® and iPhone® devices. Works over your LAN via your RJ-45 port or via an optional USBWL11N wireless adapter.

STANDARD FEATURES

MyButton



Four customizable buttons on the remote control allow users to create a shortcut for projector functions such as Information, Auto Keystone, Picture Mode etc.



Network Control, Maintenance and Security



Embedded networking gives you the ability to manage and control multiple projectors over your LAN. Features include scheduling of events, centralized reporting, image transfer and e-mail alerts for reactive and routine maintenance.

PC-Less Presentation



By using a USB memory stick or other storage device, you can use the projector without a computer. Menus are easy to see with a thumbnail display. Additionally there is also a slideshow function.

PIN Lock / MyScreen / MyText



PIN lock protection can limit projector users. MyScreen PIN lock keeps captured images on the startup screen. Users can set any name logo to MyScreen, clearly identifying ownership. MyText provides the ability to write text on the startup screen such as model name, serial number or location.

PJMessenger



PJMessenger function allows you to send and display text messages and audio alerts on your networked projectors. It is an easy and efficient way to send announcements out to multiple units.

Present Content via LAN



Hitachi's suite of networking software allows you to easily send content directly from your PC to the projector via your LAN connection.

Wireless Presentation Ready



You can use a wireless network by connecting the projector to a computer using the optional USB wireless adapter part number USBWL11N. The adapter supports IEEE802.11b/g and the latest 11n.

CP-X8150 LCD Projector

HITACHI
Inspire the Next

Quality, reliability and installation convenience.

From mid-size to very large auditoriums and conference halls, Hitachi's CP-X8150 LCD projector is the perfect solution. With 5,000 ANSI lumens brightness and XGA 1024 x 768 resolution, the CP-X8150 will deliver dynamic images guaranteed to dazzle any audience. Incorporating Hitachi's leading-edge technology, the CP-X8150 features high contrast ratio, long lamp life, a variety of lens options to accommodate your specific application, and is wireless presentation ready. Plus, embedded



networking gives you the ability to manage and control multiple projectors over your LAN (scheduling of events, centralized reporting, image transfer, and e-mail alerts). Even with the array of advanced features, Hitachi's CP-X8150 is designed for user-friendly operation and installation convenience.



Front 3/4 View



Top View




Side Profile



Rear View

Input/Outputs



- | | | |
|--------------------|---------------------|-----------------------|
| 1. USB Type A x 2 | 8. Audio in 1 | 15. Control (RS-232C) |
| 2. USB Type B | 9. Audio in 2 | 16. Remote Control |
| 3. Composite Video | 10. Security Bar | 17. AC Inlet |
| 4. HDMI x 2 | 11. Monitor Out | 18. Remote Sensor |
| 5. Audio in 3 | 12. Component | 19. S-Video |
| 6. Computer in 2 | 13. Kensington Lock | 20. LAN |
| 7. Computer in 1 | 14. Audio Out | |



3LCD Technology



Closed Captioning



Crestron Integrated Partner



AMX Device Discovery



Hitachi Trade-Up Program



3 Year Warranty

HDMI HDMI

HI0113-Rev.1-07/13
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2013 Hitachi America, Ltd. All Rights Reserved.

Hitachi America, Ltd.
900 Hitachi Way, Chula Vista, CA 91914
Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors

CP-X8150



Accessories and Lenses

Supplied Accessories	Remote control, power cord, computer cable, one standard SL702 lens, lens cover, user's manual, security label, application CD, adapter cover
Optional Accessories	USBWL11N USB wireless adapter, MS-1 wired multifunction switcher, MS-1WL wireless multifunction switcher
Optional Lenses	4 optional lenses are available: FL701, ML703, LL704, UL705
Replacement Parts	
Lamp	DT01281
Remote Control	HL02801
Filter	MU06642

Projection Throw Chart

Screen Size 4:3		Throw Distance	
Diagonal	Width	Min	Max
30	24	37	55
60	48	73	109
80	64	96	145
100	80	120	181
150	120	180	271
200	160	239	361
250	200	299	451
300	240	359	541

Throw Ratio: 1.5 - 2.2 : 1 (distance : width)
Screen size and throw distance are measured in inches with standard lens SL702.

Projection Lens Chart

Lens	Inches	Meters
SL702	120 - 181	3.1 - 4.6
FL701	83	2.1
ML703	153 - 303	3.9 - 7.7
LL704	288 - 490	7.3 - 12.4
UL705	487 - 830	12.4 - 21.1

Projection distances measured in inches and meters with standard lens and optional lenses when projecting onto a 100" diagonal screen.

Specifications

Display	Projection Technology	3LCD, 3 chip technology	
	Resolution	XGA 1024 x 768	
	White Light Output	5,000 ANSI lumens	
	Color Light Output	5,000 ANSI lumens	
	Colors	16.7 million colors	
	Aspect Ratio	Native 4:3 / 16:9 and 16:10 compatible	
Lens & Operation	Contrast Ratio	3000 : 1 (using active IRIS)	
	Throw Ratio (distance : width)	1.5 - 2.2:1 (with standard lens)	
	Lens	F = 1.6 - 2.0, f = 19 - 29 mm x 1.2 motorized zoom, focus & lens shift	
	Lamp Wattage	245W	
	Expected Lamp Life*	Approximately 2,500 hours (standard mode) 4,000 hours (Eco mode)	
	Expected Filter Life**	Approximately 15,000 hours	
	Speaker Output	16W (8W x 2 stereo)	
	Acoustic Noise Level	35 dB (29 dB in Eco mode)	
	Keystone	H and V: +/- 35° (with standard lens)	
	Compatibility	Computer	VGA, SVGA, XGA, WXGA/WXGA+/SXGA/SXGA+/UXGA (compressed), MAC 16"
H-Sync		31.5 kHz - 106 kHz	
V-Sync		56 Hz - 120 Hz	
Composite Video		NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM	
Component Video		480i, 480p, 576i, 720p, 1080i, 1080p	
Connectors	HDMI	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS clock 27 MHz - 150 MHz	
	Digital Input	HDMI x 2 (HDCP compliant)	
	Computer Input 1	15-pin mini D-sub x 1	
	Computer Input 2	BNC x 5	
	Computer Monitor Output	15-pin mini D-sub x 1	
	Video Input		
	S-Video	Mini DIN 4-pin x 1	
	Composite Video	RCA jack x 1	
	Component Video	RCA jack x 3, 15-pin mini D-sub x 1 (shared with computer in 1) BNC x 3 (shared with computer in 2)	
	Audio Input	3.5 mm stereo mini jack x 2, RCA jack (L/R) x 1	
	Audio Output	RCA jack (L/R) x 1	
	Network LAN Wired	RJ-45 port (100 base-T / 100 base-TX)	
	Network LAN Wireless	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	
	USB	Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control)	
	Control Terminals	9-pin D-sub x 1 (RS-232 control)	
	Ratings & Warranty	Power Supply	AC100-120V / AC220-240V, 50/60Hz
		Power Consumption	375W
Operating Temperature		32°F - 104°F (0°C - 40°C)	
Dimensions (W x D x H)		19.6" x 15.6" x 5.3" (without lens)	
Weight		Approximately 18.3 lbs.	
Approvals		UL 60950-1 / cUL, FCC Part 15 subpart B class A	
Warranty	3 year limited parts and labor Extended Service Contract available (additional cost)		

